



Compliant

DS

R10

MSR-A2

underlayer)

< 0.2 mm (*with underlayment) < 0.15 % (80 °C/6 h)

< 2 kV (antistatic)

17 ∆Lw dB (Integrated cork

JASPER CLA 200

SPECIAL ORDER: Inspired by the rugged back country trails of Jasper National Park. When the sunrise hits the brown and grey shades to create the rugged but warm nuances. Creates an incredible rustic atmosphere in any space.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Hybrid Flooring / Click PVC Free LVT	CARB2
Article Number / EAN Code	LTAWAW1116 / 6438117716745	Residual indentation
Design	1-strip	
Width x Length x Thickness	200 x 1815 x 9 mm	Dimensional stability
Weight per package / per	15.84 kg / 7.3 kg	Slip resistance
m2		Slip resistance
Area per package / per	2.17 m ² / 104.16 m ²	Statical electrical
pallet		propensity
Joint	Uniclic®	Scratch resistance
Installation method	Floating	Impact sound reduction
Floor heating	Yes	
Warranty	30 years residential/15 years commercial	.40N C/
TECHNICAL PROPERTIES		M1) A+ score

EN ISO 10874

EN13501-1

EN717-1

EN12664

MISSION CLASS
± M1 > 2
ë. 1
SALM DHIO,







EN ISO 24343-1

EN ISO 23999

EN 13893

DIN 51130

EN 1815

EN16094

EN ISO 10140



DETAILED DESCRIPTION

Thermal Conductivity

Formaldehyde Emission

Emission of formaldehyde

Application

Reaction To Fire

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

CL 23/33

0.118 W/(m*K)

E1 Cfl-s1

E1

Other products in this collection



SERENGETI CLA 200



ROCKY CLA 200



YELLOWSTONE CLA 200



SMOKY CLA 200



GRAND CANYON CLA 200



KAPPADOKIEN CLA 200



BWINDI CLA 200



JASPER CLA 200



YOSEMITE CLA 200