



JASPER CLA 200

Inspired by the rugged back country trails of Jasper National Park. When the sunrise hits the brown and grey shades to create the rugged but warm nuances. Creates an incredible rustic atmosphere in any space.

PRODUCT DETAILS

| | |
|--------------------|-----------------------|
| Article Number | LTAWAW1116 |
| Dimensions | 200 x 1815 mm |
| Weight per Package | 15.84 kg |
| Area per Package | 2.17 m ² |
| Area per pallet | 104.16 m ² |
| | HDF Click |






DETAIL DESCRIPTION

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

FACTS

| | |
|---------------|------------------|
| Design | Wood design |
| Range | Luxury Tiles |
| Collection | Aware Collection |
| Floor heating | Yes |

TECHNICAL PROPERTIES


| | | |
|--------------------------------|----------------|---|
| Application | EN ISO 10874 | CL 23/33 |
| Emission of formaldehyde | | E1 |
| Reaction To Fire | EN13501-1 | Cfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Thermal Conductivity | EN12664 | 0.118 W/(m*K) |
| CARB2 | | Compliant |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with underlayment)  |
| Dimensional stability | EN ISO 23999 | < 0.15 % (80 °C/6 h)  |
| Slip resistance | EN 13893 | DS  |
| Slip resistance | DIN 51130 | R10  |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic)  |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

| | | | |
|------------------------|--------------|--|---|
| Scratch resistance | EN16094 | MSR-A2 |  |
| Impact sound reduction | EN ISO 10140 | 17 ΔLw dB (Integrated cork underlayer) |  |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



25.02.2024

AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2023

Other products in this collection



Serengeti CLA 200



Rocky CLA 200



Yellowstone CLA 200



Smoky CLA 200



Grand Canyon CLA 200



Kappadokien CLA 200



Bwindi CLA 200



Jasper CLA 200



Yosemite CLA 200

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

