

# JATOBA LA PAZ

Jatoba La Paz is a dark, somewhat reddish floor.

### PRODUCT DETAILS

|                             |                                 | reening/ening/enings                |             |            |
|-----------------------------|---------------------------------|-------------------------------------|-------------|------------|
| Product type / Construction | Wood Floors / 3-layer parquet   | Moisture content                    | EN13183     | 7%±2%      |
| Article Number / EAN Code   | 153N15JO50KW240 / 7393969301053 | Minimun Mean Density                |             | >500 kg/m³ |
| Design / Wood Species       | 3-strip / Jatoba                | kg/m <sup>3</sup>                   |             |            |
| Surface treatment /         | Satin lacquer / Natural         | Reaction To Fire                    | EN13501-1   | Dfl-s1     |
| Natural/Stained             |                                 | Formaldehyde Emission               | EN717-1     | E1         |
| Width x Length x Thickness  | 200 x 2423 x 15 mm              | Content PCP                         | CEN/TR14823 | ≤ 5 ppm    |
| Weight per package / per    | 27.5 kg / 9.45 kg               | Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD        |
| m2                          |                                 | Thermal Conductivity                | EN12664     | 0,11W/mK   |
| Area per package            | 2.91 m <sup>2</sup>             | Biological Durability               | EN350-2     | Class 1    |
| Grading                     | Calm                            | CARB2                               |             | Compliant  |
| Joint                       | Woodloc® 5S                     | Slip resistance                     | CEN/TS15676 | NPD        |
| Installation method         | Floating, Glue-down             | 100 C                               |             |            |
| Floor heating               | Yes                             |                                     |             |            |
| Wear leayer material /      | Hardwood / 3.5 mm               | CARB P2<br>Compliant                |             |            |
| thickness                   |                                 |                                     |             |            |
| Resandable                  | 2-3 times                       |                                     |             |            |
| Core material               | Pine/Spruce lamella             |                                     |             |            |
| Hardness (Brinell) value /  | 7,0 / 4.5 - 14.1                |                                     |             |            |
| range                       |                                 |                                     |             |            |
| Warranty                    | 30 years                        |                                     |             |            |

**TECHNICAL PROPERTIES** 

### DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark red.

Small sized knots in limited numbers allowed.

Colour change: Pronounced deepening and darkening of colors. Yellowish and white spot may occur.

Packages may contain start and stop boards.

#### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## www.kahrs.com | <sup>©</sup>Kährs {year}