



OAK GHOST

The semi-transparent white stain on this single-strip oak floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the subtle warm oak tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N51EKB4KW220	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969301589	Design	1-strip	content		
Surface treatment	Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles.	Grading	Lively	Minimun Mean	>500 kg/m³	
		Range	Kährs Original	Reaction To Fire Formaldehyde Emission	EN13501-1	Dfl-s1
		Collection	Lux Collection		EN717-1	E1
		Resandable	2-3 times			
Design features	Microbevelled 4-sided, Brushed	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 ppm
Dimensions	151 x 2266 mm	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	16.4 kg	Joint	Woodloc® 5S			
Area per Package	2.05 m ²	Floor heating	Yes	Thermal Conductivity	EN12664	0,14 W/mK
Area per pallet	110.7 m ²	Warranty	30 years			
Package info	Packages may contain start and stop boards.	Warranty US	25 years	Thermal Resistance R-Value		.11 (m2K/W)
		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
DETAIL DESCRIPTION		Wear Layer Thickness	3.5 mm	CARB2		Compliant
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers. Thickness of the product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.		Core material	Pine/Spruce/Alder	Slipperiness		
		Thickness	15 mm	_ Suppermess CLIV/1313070) NFD
		Installation method	Floating, Glue-down			
		Surface Colour	White			
		LRV	46			

Stained product - noticeable color change over time

COLOUR CHANGE

Other products in this collection



CERTIFICATES



















Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.