



OAK CALM

OAK CALM flooring has a serene semi-transparent stain that blends with the light oak tones, highlighting the natural knots and cracks. The brushed and beveled boards enhance the wood's texture, while the matt lacquer finish provides protection and a natural look. It's a timeless and elegant option that showcases the natural beauty of the wood.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	141XCDEK2VKW195 / 7393969301718
Design / Wood Species	1-strip / Oak
Surface Treatment / Natural/Stained	Matt lacquer / Stained
Refining Treatment	Microbevelled 4-sided, Brushed
Width x Length x Thickness	190 x 1900 x 14 mm
Weight per package / per m2	22.18 kg / 7.7 kg
Area per package / per pallet	2.88 m ² / 129.6 m ²
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear layer material / thickness	Hardwood / 2.7 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Backside material	Veneer

PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1 / LRV Std2	38 / 5.8 / 11.6
Warranty	30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Biological Durability	EN350-2	Class 1



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK WISDOM



OAK HAPPINESS



OAK CALM



OAK STRENGTH