



OAK STRENGTH

The OAK STRENGTH floor has a soft white stain, organic expression with knots and cracks, brushed and beveled boards highlighting the natural texture. The matte lacquer finish protects against wear and eliminates glare creating a modern charm.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	141XCDEK1WKW195 / 7393969301725
Design / Wood Species	1-strip / Oak
Surface Treatment / Natural/Stained	Matt lacquer / Stained
Refining Treatment	Microbevelled 4-sided, Brushed
Width x Length x Thickness	190 x 1900 x 14 mm
Weight per package / per m2	22.18 kg / 7.7 kg
Area per package / per pallet	2.88 m ² / 129.6 m ²
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 2.7 mm
Resandable	2-3 times
Core material	Pine/Spruce
Backside material	Veneer

PRODUCT DETAILS		
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9	
LRV / LRV Std1 / LRV Std2	50 / 2.2 / 4.4	
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimum Mean Density	>500 kg/m³	
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Biological Durability	EN350-2	Class 1



Other products in this collection



OAK WISDOM



OAK HAPPINESS



OAK CALM



OAK STRENGTH