

## COCONINO CLW 218

Kährs Rigid Click Luxury Tiles floor Coconino has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by registered embossing.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Thermal Resistance R-Value		0.035 (m2K/W)
Article Number / EAN Code	LTCLW2310-218 / 7393969301527		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
Design	Tile Design		_		underlayment)
Width x Length x Thickness	218 x 1210 x 6 mm		Dimensional stability	EN ISO 23999	< 0.1 %
Weight per package / per	20.6 kg / 9.81 kg		Colour fastness	EN ISO 105-B02	≥ 6
m2			Slip resistance	EN 13893	DS (>0.3)
Area per package / per	2.1 m <sup>2</sup> / 84.4 m <sup>2</sup>		Slip resistance	DIN 51130	R10
pallet			Statical electrical	EN 1815	< 2 kV (antistatic)
Joint	Click5G		propensity		
Installation method	Floating		Scratch resistance	EN16094	Pass with good results
Floor heating	Yes		Chemical resistance	EN ISO 26987	Pass with good results
Wear leayer thickness	0.55 mm		Resistance to bacteria and		Good
Warranty	30 years residential/15 years commercial		fungi		
TECHNICAL PROPERTIES			Impact sound reduction	EN ISO 10140	20 <b>∆</b> Lw dB (IXPE underlayment)
Application	EN ISO 10874	23/33/42	- Commercial usage	EN 14354:2017	Class 33
Emission of formaldehyde		E1	- classification	LIN 14334.2017	CI 222 22
Reaction To Fire	EN13501-1	Bfl-s1			
Formaldehyde Emission	EN717-1	E1	- M12 score (	CALIFICACIÓN DE CONSTRUCTION	

## DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | <sup>©</sup>Kährs, United Kingdom & Ireland 2025-07-16

## Other products in this collection



MOESGAARD - CLICK 6 MM



OTAGO - CLICK 6 MM



FOLOI - CLICK 6 MM



THURINGIAN - CLICK 6 MM



AKKELIS - CLICK 6 MM



KILSBERGEN - CLICK 6 MM



COCONINO - CLICK 6 MM



TAKAYNA - CLICK 6 MM



DIDNOK - CLICK 6 MM



BLAIKEN - CLICK 6 MM