



THURINGIAN CLW 218

Kährs Luxury Tiles Click floor Thuringian has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by synchrone embossing.

PRODUCT DETAILS			TE
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2311-218 / 7393969301534		
Design	Tile Design		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		Dir
m2			Со
Area per package / per	2.11 m ² / 84.4 m ²		Sli
pallet			Sli
Joint	Click5G		Sta
Installation method	Floating		pro
Floor heating	Yes		Sci
Wear leayer thickness	0.55 mm		Ch
Warranty	30 years residential/15 years commercial		Eff
TECHNICAL PROPERTIES			Re
Application	EN ISO 10874	23/33/42	fur
Effect of furniture leg	EN ISO 16581	No visible damage/Change	- Im
Emission of formaldehyde		E1	
Reaction To Fire	EN13501-1	Bfl-s1	— Co

	12011110112111012111120		
	Formaldehyde Emission	EN717-1	E1
	Thermal Resistance R-Value		0.035 (m2K/W)
	Residual indentation EN		< 0.2 mm (*with
	ISO 24343-1		underlayment)
	Dimensional stability	EN ISO 23999	< 0.1 %
	Colour fastness	EN ISO 105-B02	≥ 6
	Slip resistance	EN 13893	DS (>0.3)
	Slip resistance	DIN 51130	R10
	Statical electrical	EN 1815	< 2 kV (antistatic)
	propensity		
	Scratch resistance	EN16094	Pass with good results
	Chemical resistance	EN ISO 26987	Pass with good results
	Effect of castor chair	EN 425	Suitable
	Resistance to bacteria and		Good
_	fungi		
_	Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
_			underlayment)
	Commercial usage	EN 14354:2017	Class 33
	classification		













DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



MOESGAARD - CLICK 6 MM



THURINGIAN - CLICK 6 MM



COCONINO - CLICK 6 MM



DIDNOK - CLICK 6 MM



OTAGO - CLICK 6 MM



AKKELIS - CLICK 6 MM



TAKAYNA - CLICK 6 MM



BLAIKEN - CLICK 6 MM



FOLOI - CLICK 6 MM



KILSBERGEN - CLICK 6 MM