



THURINGIAN CLICK 6 MM

Kährs Luxury Tiles Click floor Thuringian has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by synchrone embossing.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	Reaction To Fire	EN13501-1	Bfl-s1
Article Number / EAN Code	LTCLW2311-218 / 7393969301534	Formaldehyde Emission	EN717-1	E1
Design	Plank	Thermal Resistance R-Value		0.035 (m2K/W)
Width x Length x Thickness	218 x 1210 x 6 mm	Residual indentation EN		< 0.2 mm (*with
Weight per package / per	20.6 kg / 9.81 kg	ISO 24343-1		underlayment)
m2		Dimensional stability	EN ISO 23999	< 0.1 %
Area per package / per	2.11 m ² / 84.4 m ²	Colour fastness	EN ISO 105-B02	≥ 6
pallet		Slip resistance	EN 13893	DS (>0.3)
Joint	Click5G	Slip resistance	DIN 51130	R10
Installation method	Floating	Statical electrical	EN 1815	< 2 kV (antistatic)
Floor heating	Yes	propensity		
Wear leayer thickness	0.55 mm	Scratch resistance	EN16094	Pass with good results
Warranty	30 years residential/15 years commercial	Chemical resistance	EN ISO 26987	Pass with good results
TECHNICAL PROPERTIES		Effect of castor chair	EN 425	Suitable (25.000 cycles)
Application	EN ISO 10874	23/33/42		
Effect of furniture leg	EN ISO 16581	No visible damage/Change		
Impact resistance		>1800 mm		
Emission of formaldehyde		E1		
		Resistance to bacteria and		Good
		fungi		
		Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE
				underlayment)
		Commercial usage	EN 14354:2017	Class 33
		classification		



DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



MOESGAARD CLICK



THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK



AKKELIS CLICK



TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK