

**FACTS** 



**TECHNICAL PROPERTIES** 

# THURINGIAN CLW 218

PRODUCT DETAILS

Kährs Luxury Tiles Click floor Thuringian has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by synchrone embossing.

PRODUCT DETAILS		FAC13		TECHNICAL PROPE	KIIES		
Article Number	LTCLW2311-218	Design	Wood design	Application	EN ISO	23/33/42	
Design features	Microbevelled 4- sided	Features	Antistatic, Sound reducing, Floor	Effect of	10874 EN ISO	No visible	
Dimensions	218 x 1210 mm		covering	furniture leg	16581	damage/Change	ž
Weight per Package	20.6 kg	Format	Planks	Emission of		E1	
Area per Package	2.1 m <sup>2</sup>	Range	Luxury Tiles	formaldehyde			- CAD
Area per pallet	84.4 m <sup>2</sup>	Collection	Nordic Classic Collection	Reaction To Fire	EN13501- 1	Bfl-s1	B <sub>ir</sub> s1
Construction	Click 6 mm	Joint	Click5G	Formaldehyde Emission	EN717-1	E1	
DETAIL DESCRIPTION		Warranty	30 years residential/15 years commercial	Thermal Resistance R- 0.039 Value		0.035 (m2K/W)	
For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.		Backside material	IXPE Sound reducing backing			< 0.2 mm (*with underlayment)	
		Thickness	6 mm	Dimensional stability	EN ISO 23999	< 0.1 %	K N K N
		Installation method	Floating	Colour fastness	EN ISO 105-B02	≥ 6	<b>\$</b>
				Slip resistance	EN 13893	DS (>0.3)	7.5 0s
				Slip resistance	DIN	R10	

# **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











51130

#### **TECHNICAL PROPERTIES**

I ECHINICAL PROPI	KIILJ		
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	Ť
Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	<b>₽</b>
Effect of castor chair	EN 425	Suitable	<b>a</b>
Resistance to ba	cteria and	Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
Commercial usage classification	EN 14354:2017	Class 33	

### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











# Other products in this collection



Kilsbergen - Click 6 mm

Irati - Click 6 mm

#### **Descriptions & Imagery**

Foloi - Click 6 mm

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











Pando - Click 6 mm

