



MOESGAARD CLICK 6 MM

Kährs Luxury Tiles Click floor Moesgaard has a light natural oak design, softened by a transparent white stain, resulting in a timeless floor that complements any interior. The natural oak colour, wood grain and visible knots and cracks create an authentic look, enhanced by synchrone embossing.

PRODUCT DETAILS		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	
Article Number / EAN Code	LTCLW2312-218 / 7393969301541	
Design	Plank	
Width x Length x Thickness	218 x 1210 x 6 mm	
Weight per package / per	20.6 kg / 9.81 kg	
m2		
Area per package / per	2.11 m ² / 84.4 m ²	
pallet		
Joint	Click5G	
Installation method	Floating	
Floor heating	Yes	
Wear leayer thickness	0.55 mm	
Warranty	30 years residential/15 years commercial	
TECHNICAL PROPERTIES		
Application	EN ISO 10874	23/33/42
Effect of furniture leg	EN ISO 16581	No visible damage/Change
Emission of formaldehyde		E1
Reaction To Fire	EN13501-1	Bfl-s1

TECHNICAL I NOI ENTIES		
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
•		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

DDODLICT DETAILS

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

Other products in this collection





THURINGIAN CLICK



COCONINO CLICK



DIDNOK CLICK



OTAGO CLICK





TAKAYNA CLICK



BLAIKEN CLICK



FOLOI CLICK



KILSBERGEN CLICK