



OAK YARROW

A light stain is used to give Oak Yarrow its modern, slightly muted look, reminiscent of freshly cut oak timber. The oiled surface, brushed to soften the cracks and knots, allows each board to demonstrate the natural wood grain of the material while still retaining the subtlety of this floor – in both its visual and tactile impression.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	131245220 / 7393969302470	range		
Design / Wood Species	1-strip / Oak	LRV / LRV Std1 / LRV Std2	36 / 4.9 / 9.8	
Surface Treatment /	Oil / Stained	Warranty	20 years	
Natural/Stained		TECHNICAL PROPERTIES		
Refining Treatment	Microbevelled 4-sided, Brushed	Moisture content	FN13183	7%±2%
Width x Length x Thickness	187 x 2266 x 13 mm	Minimun Mean Density	LIVISIOS	>500 kg/m ³
Weight per package / per	24 kg / 7.2 kg	kg/m ³		- 500 kg/III
m2		Reaction To Fire	EN13501-1	Dfl-s1
Area per package / per	3.39 m ² / 152.55 m ²	Formaldehyde Emission	EN717-1	E1
pallet		Content PCP	CFN/TR14823	≤ 5 x 10-6n
Grading	Dynamic	Breaking Strength N/mm²	EN1533	NPD
Joint	Woodloc® 5G	——— Thermal Resistance R-Value		.09 (m2K/W)
Installation method	Floating, Glue-down	Biological Durability	EN350-2	Class 1
Floor heating	Yes	CARB2	LINDOU Z	Compliant
Wear leayer material /	Hardwood / 2.6 mm	Slip resistance	CEN/TS15676	NPD
thickness		Slip resistance	CEIV/1313070	NI D
Resandable	2 times	(MARKONS CANS LINE RYTHEU)		
Core material	Pine/Spruce lamella	A+		
Backside material	Spruce			

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Packages may contain start and stop boards.

Other products in this collection





OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED