



OAK YARROW

DDODLICT DETAIL C

A light stain is used to give Oak Yarrow its modern, slightly muted look, reminiscent of freshly cut oak timber. The oiled surface, brushed to soften the cracks and knots, allows each board to demonstrate the natural wood grain of the material while still retaining the subtlety of this floor – in both its visual and tactile impression.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	131245220 / 7393969302470	range
Design / Wood Species	1-strip / Oak	LRV / LRV Std1 / LRV Std2
Surface Treatment /	Oil / Stained	Warranty
Natural/Stained		TECHNICAL PROPERTIE
Refining Treatment	Microbevelled 4-sided, Brushed	——— Moisture content
Width x Length x Thickness	187 x 2266 x 13 mm	Minimun Mean Density
Weight per package / per	24 kg / 7.2 kg	kg/m ³
<u>m2</u>		——— Reaction To Fire
Area per package / per	3.39 m ² / 152.55 m ²	Formaldehyde Emission
pallet		——— Content PCP
Grading	Dynamic	Breaking Strength N/mm²
Joint	Woodloc® 5G	Biological Durability
Installation method	Floating, Glue-down	CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 2.6 mm	Ship resistance
thickness		SPESIONI DANS LINE RETERENE
Resandable	2 times	A+
Core material	Pine/Spruce	
Backside material	Spruce	

PRODU	JCT [DETAI	LS
-------	-------	-------	----

	-/	
range		
LRV / LRV Std1 / LRV Std2	36 / 4.9 / 9.8	
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

3,7 / 2.2 - 5.9





DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Packages may contain start and stop boards.

Other products in this collection



OAK YARROW



OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED



OAK PRIMROSE



OAK LUPINE



OAK LAVENDER



OAK ZINNIA