



OAK ASTER OILED 226

The natural oak design of Oak Aster is beautiful in its own right without any additional staining. Natural by design, the warm colours of the oak are able to penetrate the oiled surface completely uninhibited. Each board is carefully brushed, accentuating the natural wood grain while softening the texture, knots and cracks. Any contrast in colour is purely natural, letting the raw material speak for itself. Oak Aster is also available in a matt lacquered finish.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	131246220 / 7393969302494	range		
Design / Wood Species	1-strip / Oak	LRV / LRV Std1 / LRV Std2	40 / 4.4 / 8.8	
Surface Treatment /	Oil / Natural	Warranty	20 years	
Natural/Stained		TECHNICAL PROPERTIES	:	
Refining Treatment	Microbevelled 4-sided, Brushed	Moisture content	FN13183	7%±2%
Width x Length x Thickness	187 x 2266 x 13 mm	Minimun Mean Density	LIVISIOS	>500 kg/m ³
Weight per package / per	24 kg / 7.2 kg	kg/m ³		>300 Kg/III
m2		Reaction To Fire	EN13501-1	Dfl-s1
Area per package / per	3.39 m ² / 152.55 m ²	Formaldehyde Emission	EN717-1	F1
pallet		Content PCP	CFN/TR14823	≤ 5 x 10-6n
Grading	Dynamic	Breaking Strength N/mm ²	EN1533	NPD
Joint	Woodloc® 5G	Thermal Resistance R-Value		.09 (m2K/W)
Installation method	Floating, Glue-down		EN350-2	Class 1
Floor heating	Yes	——— Biological Durability CARB2	EIN53U-Z	Compliant
Wear leayer material /	Hardwood / 2.6 mm		CENTE 1 F C 7 C	<u> </u>
thickness		Slip resistance	CEN/TS15676	NPD
Resandable	2 times	SANDONI CANE LAN BYTTEEST		
Core material	Pine/Spruce lamella	A+		
Backside material	Spruce			

DETAILED DESCRIPTION

Oil: This floor should be oiled immediately after installation.

Packages may contain start and stop boards.

Other products in this collection





OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED