



OAK LECCO ULTRA MATT

Warm brown tones blend with caraway seed hues in this 3-strip oak floor from the Tres Collection. The planks have been specially selected with very few knots for a calm and even appearance. Each board is carefully brushed to perfection, bringing out the faintly burnished nuances in the grain. The ultra matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--------------------|---|----------------------|---------------------|---------------------------------------|-------------|-----------|
| Article Number | 133N1BEK04KW240 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| EAN Code | 7393969302296 | Design | 3-strip | Minimum Mean Density kg/m³ >500 kg/m³ | | |
| Surface treatment | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. | Grading | Variation | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Dimensions | 200 x 2423 mm | Range | Kährs Avanti | Formaldehyde Emission | EN717-1 | E1 |
| | | Collection | Tres collection | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Weight per Package | 24.5 kg | Resandable | 2-3 times | Breaking Strength N/mm² | EN1533 | NPD |
| Area per Package | 3.4 m² | Natural/Stained | Natural | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Area per pallet | 170 m² | Brinell Value | 3,7 | Thermal Resistance R-Value | .09 (m2K/W) | |
| Package info | Packages may contain start and stop boards. | Joint | Woodloc® 5G | Biological Durability | EN350-2 | Class 1 |
| DETAIL DESCRIPTION | | Floor heating | Yes | CARB2 | Compliant | |
| | | Warranty | 20 years | Slipperiness | CEN/TS15676 | NPD |
| | | Warranty US | 20 years | | | |
| | | Wear-layer material | Hardwood | | | |
| | | Wear Layer Thickness | 2.6 mm | | | |
| COLOUR CHANGE | | Core material | Pine/Spruce/Alder | | | |
| | | Thickness | 13 mm | | | |
| | | Installation method | Floating, Glue-down | | | |

Some muting of colour variation to medium, straw brown.

Other products in this collection



Oak Cortina



Oak Vanilla



European Maple Gotha



Red Oak Nature



Ash Ceriale



Ash Vaila



Oak Bisbee



Oak Supai



Oak Pima



Oak Erve



Oak Abetone



Oak Lecco

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.