



## **OAK EDELWEISS**

Oak Edelweiss creates a light, timeless impression in the interior, allowing the translucent, white-tinted oil to soften the contrast of knots and cracks in the floor. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the wood.

| PRODUCT DETAILS             |   | PRODUCT DETAILS            |                 |             |
|-----------------------------|---|----------------------------|-----------------|-------------|
| Product type / Construction | Wood Flooring / 3-layer parquet             | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 |             |
| Article Number / EAN Code   | 131247220 / 7393969302517                   | range                      |                 |             |
| Design / Wood Species       | 1-strip / Oak                               | LRV / LRV Std1 / LRV Std2  | 41 / 4.7 / 9.4  |             |
| Surface Treatment /         | Oil / Stained                               | Warranty                   | 20 years        |             |
| Natural/Stained             |   | TECHNICAL PROPERTIES       |                 |             |
| Refining Treatment          | Microbevelled 4-sided, Brushed              | —— Moisture content        | EN13183         | 7%±2%       |
| Width x Length x Thickness  | 187 x 2266 x 13 mm                          |                            | EINIOIOO        |             |
| Weight per package / per    | 23 kg / 7.2 kg                              | Minimun Mean Density       |                 | >500 kg/m³  |
| m2                          |   | kg/m³ Reaction To Fire     | EN13501-1       | <br>Dfl-s1  |
| Area per package / per      | 3.39 m <sup>2</sup> / 152.55 m <sup>2</sup> |                            |                 | E1          |
| pallet                      |   | Formaldehyde Emission      | EN717-1         |             |
| Grading                     | Dynamic                                     | Content PCP                | CEN/TR14823     | ≤ 5 x 10-6n |
| Joint                       | Woodloc® 5G                                 | Breaking Strength N/mm²    | EN1533          | NPD         |
| Installation method         | Floating, Glue-down                         | Thermal Resistance R-Value |                 | .09 (m2K/W) |
| Floor heating               | Yes   | Biological Durability      | EN350-2         | Class 1     |
| Wear leayer material /      | Hardwood / 2.6 mm                           | CARB2                      |                 | Compliant   |
| thickness                   |   | Slip resistance            | CEN/TS15676     | NPD         |
| Resandable                  | 2 times                                     | (MISONI DANI LAN RYTEREN)  |                 |             |
| Core material               | Pine/Spruce lamella                         | A+                         |                 |             |
| Backside material           | Spruce                                      |                            |                 |             |

## DETAILED DESCRIPTION

Oil: This floor should be oiled immediately after installation.

Packages may contain start and stop boards.

## Other products in this collection





OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED