



## **OAK EDELWEISS**

Oak Edelweiss creates a light, timeless impression in the interior, allowing the translucent, white-tinted oil to soften the contrast of knots and cracks in the floor. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the wood.

PRODUCT DETAILS		PRODUCT D
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Bri
Article Number / EAN Code	131247220 / 7393969302517	range
Design / Wood Species	1-strip / Oak	LRV / LRV Std
Surface Treatment /	Oil / Stained	Warranty
Natural/Stained		TECHNICAL
Refining Treatment	Microbevelled 4-sided, Brushed	——— Moisture con
Width x Length x Thickness	187 x 2266 x 13 mm	——— Minimun Mea
Weight per package / per	24 kg / 7.2 kg	kg/m <sup>3</sup>
m2		Reaction To F
Area per package / per	3.39 m <sup>2</sup> / 152.55 m <sup>2</sup>	Formaldehyd
pallet		Content PCP
Grading	Dynamic	Breaking Stre
Joint	Woodloc® 5G	Biological Dur
Installation method	Floating, Glue-down	CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 2.6 mm	Shp resistance
thickness		SMESSONS CANS LAW SHEETS BUT
Resandable	2 times	A+
Core material	Pine/Spruce lamella	
Backside material	Spruce	

Р	RO	DU	ICT	DE	ΓAΙ	LS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1 / LRV Std2	41 / 4.7 / 9.4	
Warranty	20 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1

9		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



## **DETAILED DESCRIPTION**

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable colour change over time.

Packages may contain start and stop boards.

## Other products in this collection





OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED