



Kährs

Flora Collection



OAK YARROW

With a light stain lightening the tone of the natural oak raw-material, a luminescent golden touch has been added to Oak Yarrow. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtlety of this floor – in both its visual and tactile impression.

PRODUCT DETAILS

| | |
|-------------------------------------|---|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 131245200 / 7393969302487 |
| Design / Wood Species | 1-strip / Oak |
| Surface treatment / Natural/Stained | Oil / Stained |
| Design features | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness | 187 x 2000 x 13 mm |
| Weight per package / per m2 | 21 kg / 7.19 kg |
| Area per package / per pallet | 2.99 m ² / 134.55 m ² |
| Grading | Dynamic |
| Joint | Woodloc® 5G |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 2.6 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Spruce |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | |
|---------------------------|----------------|
| LRV / LRV Std1 / LRV Std2 | 36 / 4.9 / 9.8 |
| Warranty | 20 years |

TECHNICAL PROPERTIES

| | | |
|--|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m ³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .09 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2024-12-11

1 (2)

Other products in this collection




OAK YARROW



OAK ASTER



OAK EDELWEISS



OAK GENTIAN