



OAK YARROW

With a light stain lightening the tone of the natural oak raw-material, a luminescent golden touch has been added to Oak Yarrow. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtilty of this floor – in both its visual and tactile impression.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------|---------------------|----------------------------|--------------|------------------------|
| Article Number | 131245200 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969302487 | Design | 1-strip | content | | |
| Surface treatment | Oil This floor should be oiled immediately after installation. | Grading | Dynamic | Minimun Mean Density kg/m | | >500 kg/m ³ |
| | | Range | Kährs Wood Classic | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Collection | Flora Collection | Formaldehyde Emission | EN717-1 | E1 |
| Design features | Microbevelled 4-sided, | Natural/Stained | Stained | | | |
| | Brushed | Brinell Value | 3,7 | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Dimensions | 187 x 2000 mm | loint | Woodloc® 5G | Breaking Strength N/mm² | EN1533 | NPD |
| Weight per Package | 21 kg | Floor heating | Yes | | | |
| Area per Package | 2.99 m ² | Warranty | 20 years | Thermal | EN12664 | 0,14 W/mK |
| Area per pallet | 134.55 m ² | | | Conductivity | EN12004 | U, 14 VV/IIIN |
| Package info | Packages may contain start and stop boards. | Wear-layer material | Hardwood | Thermal Resistance R-Value | | .09 (m2K/W) |
| | | Wear Layer Thickness | 2.6 mm | | | |
| | | Core material | Pine/Spruce lamella | Biological Durability | EN350-2 | Class 1 |
| DETAIL DESCRIPTION | | Backside material | Spruce | CARB2 | | Compliant |
| All naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | Thickness | 13 mm | Slip resistance | | |
| | | Installation method | Floating, Glue-down | | CLIV/1313070 | TO NID |
| | | LRV | 36 | | | |

COLOUR CHANGE

Stained product - noticable color change over time.

Other products in this collection









OAK YARROW

OAK ASTER

OAK EDELWEISS

OAK GENTIAN

CERTIFICATES





Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.