

# SABIANO CLW 228

A warm, light-grey wash overlays the natural light oak colour and in combination with the defined wood grain, knots and cracks creates an elegant yet rustic floor which is Sabiano

PRODUCT DETAILS		FACTS		TECHNICAL PROPI	ERTIES		
Article Number	LTCLW2402-228	Design	Wood design	Effect of furniture leg	EN ISO 16581	No visible damage/Change	0
Design features	Microbevelled 4- sided	Application area	Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public	Reaction To	EN13501-	0 0	E Birst
Dimensions	228 x 1220 mm			Fire	1		
Weight per Package	22.5 kg	space	spaces, Commercial, Office, Hospitality	Thermal Resistance R- Value		0.032 (m2K/W)	( p
Area per Package	2.5 m <sup>2</sup>				Residual indentation EN		, í
Area per pallet	110 m <sup>2</sup>	Features	Antistatic	Residual indentation EN < 0.2 mm (*with ISO 24343-1 underlayment)			
	Click 5 mm	Format	Planks	Dimensional	EN ISO	< 0.1 %	רא <sup>י</sup> צע
Construction		Range	Luxury Tiles	stability	23999	< 0.1 %	КЯ
		Collection	Ranch Collection	Colour	EN ISO	≥ 6	32
		Joint	Uniclic®	fastness	105-B02		
		Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	265 DS
		Warranty	10 years	Slip resistance	DIN 51130	R10	BS-
		Backside material	IXPE Sound reducing backing	Statical electrical	EN 1815	< 2 kV	Z
		Thickness	5 mm	propensity		(antistatic)	
				Scratch resistance	EN16094	Pass with good results	P
				Chemical resistance	EN ISO 26987	Pass with good results	<i>f</i> 0

### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



#### **TECHNICAL PROPERTIES**

Effect of castor chair	EN 425	Suitable
Resistance to ba fungi	acteria and	Good
Impact sound reduction	EN ISO 10140	19 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



18.05.2024 AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2023

## Other products in this collection





Overo CLW 228







Sabiano CLW 228



Roan CLW 228

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

