



## SABIANO CLW 228

DESCRIZIONE DEL PRODO	OTTC		(
Codice articolo / Codice	LTCLW2402-228	/ 7393969302388	
EAN			-
Design	1 Listello		
Larghezza x Lunghezza x	228 x 1220 x 5 n	nm	
Spessore			
Peso per confezione / per	22,5 kg / 9 kg		-
m2			ı
Mq. per confezione / pr	2,5 m <sup>2</sup> / 110 m <sup>2</sup>		
pallet			i
INFORMAZIONI			1
Incastro	Uniclic®		
Metodi di posa	Flottante		
Riscaldamento a pavimento	Si		
Strato superficiale spessore	0,55 mm		
CARATTERISTICHE TECNIC	CHE		
Emission of formaldehyde		E1	
Classe di reazione al fuoco	EN13501-1	Bfl-s1	
Classe di emissione di	EN717-1	E1	
formaldeide			
Resistenza termica valore R		0.032 (m2K/W)	
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with	
		underlayment)	

## CARATTERISTICHE TECNICHE

Dimensional stability	EN ISO 23999	< 0.1 %
Test Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Slip resistance	CEN/TS15676	N/A
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
<u> </u>		
Scratch resistance	EN16094	Pass with good results
Scratch resistance Resistance to bacteria and	EN16094	Pass with good results Good
	EN16094	
Resistance to bacteria and	EN16094 EN ISO 10140	
Resistance to bacteria and fungi		Good
Resistance to bacteria and fungi		Good  19 ΔLw dB (IXPE











## Altri prodotti di questa collezione







Marrone CLW 228

Sabiano CLW 228

Roan CLW 228