



# TOBIANO CLW 228

Warm, darker tones in contrast with honey-coloured oak characterizes the colour of Tobiano. Natural features such as knots and cracks emphasize the authentic rustic look of this floor which will contribute to creating a homely and relaxed interior

## PRODUCT DETAILS

|                               |   |
|-------------------------------|---|
| Product type / Construction   | Luxury Vinyl Tiles and Planks / Click SPC LVT |
| Article Number / EAN Code     | LTCLW2403-228 / 7393969302395                 |
| Design                        | Tile Design                                   |
| Width x Length x Thickness    | 228 x 1220 x 5 mm                             |
| Weight per package / per m2   | 22.5 kg / 9 kg                                |
| Area per package / per pallet | 2.5 m <sup>2</sup> / 110 m <sup>2</sup>       |
| Joint                         | Uniclic®                                      |
| Installation method           | Floating                                      |
| Floor heating                 | Yes   |
| Wear leayer thickness         | 0.55 mm                                       |
| Warranty                      | 25 years                                      |

## TECHNICAL PROPERTIES

|                                     |              |                               |
|-------------------------------------|--------------|-------------------------------|
| Effect of furniture leg             | EN ISO 16581 | No visible damage/Change      |
| Reaction To Fire                    | EN13501-1    | Bfl-s1                        |
| Thermal Resistance R-Value          |              | 0.032 (m2K/W)                 |
| Residual indentation EN ISO 24343-1 |              | < 0.2 mm (*with underlayment) |

## TECHNICAL PROPERTIES

|                                  |                |                               |
|----------------------------------|----------------|-------------------------------|
| Dimensional stability            | EN ISO 23999   | < 0.1 %                       |
| Colour fastness                  | EN ISO 105-B02 | ≥ 6                           |
| Slip resistance                  | EN 13893       | DS (>0.3)                     |
| Slip resistance                  | DIN 51130      | R10                           |
| Statical electrical propensity   | EN 1815        | < 2 kV (antistatic)           |
| Scratch resistance               | EN16094        | Pass with good results        |
| Chemical resistance              | EN ISO 26987   | Pass with good results        |
| Effect of castor chair           | EN 425         | Suitable                      |
| Resistance to bacteria and fungi |                | Good                          |
| Impact sound reduction           | EN ISO 10140   | 19 ΔLw dB (IXPE underlayment) |
| Commercial usage classification  | EN 14354:2017  | Class 33                      |



### Descriptions & Imagery

Other products in this collection



MARRONE CLW 228



OVERO CLW 228



TOBIANO CLW 228



SABIANO CLW 228



ROAN CLW 228