

EACTS



No visible damage/Change

0.032 (m2K/W)

(antistatic)

EN16094 Pass with good

results

results

Pass with good

EN 1815 < 2 kV

EN ISO

26987

< 0.2 mm (*with underlayment)

TECHNICAL DEODEDTIES

Statical

Scratch resistance

Chemical resistance

electrical

propensity

TOBIANO CLW 228

DRODUCT DETAILS

Warm, darker tones in contrast with honey-coloured oak characterizes the colour of Tobiano. Natural features such as knots and cracks emphasize the authentic rustic look of this floor which will contribute to creating a homely and relaxed interior

RODUCT DETAILS		FACIS		TECHNICAL PROPI	EKITES	
Article Number	LTCLW2403-228	Design	Wood design	Effect of	EN ISO	No visible
Design features	Microbevelled 4- sided	Application area	Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality Antistatic	furniture leg Reaction To	16581 EN13501-	damage/C - Bfl-s1
Dimensions	228 x 1220 mm			Fire	1	
Weight per Package	22.5 kg	Features		Thermal Resistance R- Value		0.032 (m2
Area per Package	2.5 m ²					< 0.2 mm
Area per pallet	110 m ²					underlayn
Construction	Click 5 mm	Format	Planks	Dimensional stability	EN ISO 23999	< 0.1 %
		Range	Luxury Tiles			
		Collection	Ranch Collection	Colour	EN ISO	≥ 6
		Joint	Uniclic®	fastness 105-	105-B02	,02
		Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)
		Warranty	10 years	Slip resistance	DIN 51130	R10

Backside material

Thickness

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

IXPE Sound reducing

backing

5 mm















TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable	a
Resistance to ba	Good		
Impact sound reduction	EN ISO 10140	19 Δ Lw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33 7	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















Other products in this collection







Overo CLW 228



Tobiano CLW 228



Sabiano CLW 228



Roan CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.













