



# OVERO CLICK 5 MM

Overo features a warm aged oak colour, which in combination with the visible knots, cracks and wood grain introduces a characteristic floor lifting up any interior by creating a warm and inviting space

## PRODUCT DETAILS

|                               |   |
|-------------------------------|---|
| Product type / Construction   | Luxury Vinyl Tiles and Planks / Click SPC LVT |
| Article Number / EAN Code     | LTCLW2404-228 / 7393969302401                 |
| Design                        | Plank   |
| Width x Length x Thickness    | 228 x 1220 x 5 mm                             |
| Weight per package / per m2   | 22.5 kg / 9 kg                                |
| Area per package / per pallet | 2.5 m <sup>2</sup> / 110 m <sup>2</sup>       |
| Joint                         | Uniclic®                                      |
| Installation method           | Floating                                      |
| Floor heating                 | Yes   |
| Wear leayer thickness         | 0.55 mm                                       |
| LRV / LRV Std1 / LRV Std2     | 24 / 3 / 6                                    |
| Warranty                      | 25 years                                      |

## TECHNICAL PROPERTIES

|                          |              |                          |
|--------------------------|--------------|--------------------------|
| Effect of furniture leg  | EN ISO 16581 | No visible damage/Change |
| Emission of formaldehyde |              | E1                       |
| Reaction To Fire         | EN13501-1    | Bfl-s1                   |

## TECHNICAL PROPERTIES

|                                     |                |                               |
|-------------------------------------|----------------|-------------------------------|
| Formaldehyde Emission               | EN717-1        | E1                            |
| Thermal Resistance R-Value          |                | 0.032 (m2K/W)                 |
| Residual indentation EN ISO 24343-1 |                | < 0.2 mm (*with underlayment) |
| Dimensional stability               | EN ISO 23999   | < 0.1 %                       |
| Colour fastness                     | EN ISO 105-B02 | ≥ 6                           |
| Slip resistance                     | EN 13893       | DS (>0.3)                     |
| Slip resistance                     | DIN 51130      | R10                           |
| Slip resistance                     | CEN/TS15676    | N/A                           |
| Statical electrical propensity      | EN 1815        | < 2 kV (antistatic)           |
| Scratch resistance                  | EN16094        | Pass with good results        |
| Chemical resistance                 | EN ISO 26987   | Pass with good results        |
| Effect of castor chair              | EN 425         | Suitable                      |
| Resistance to bacteria and fungi    |                | Good                          |
| Impact sound reduction              | EN ISO 10140   | 19 ΔLw dB (IXPE underlayment) |
| Commercial usage classification     | EN 14354:2017  | Class 33                      |



## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection



MARRONE CLICK



OVERO CLICK



TOBIANO CLICK



SABIANO CLICK



ROAN CLICK