



OVERO CLW 228

Overo features a warm aged oak colour, which in combination with the visible knots, cracks and wood grain introduces a characteristic floor lifting up any interior by creating a warm and inviting space

PRODUCT DETAILS

| | |
|-------------------------------|---|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Click SPC LVT |
| Article Number / EAN Code | LTCLW2404-228 / 7393969302401 |
| Design | Tile Design |
| Width x Length x Thickness | 228 x 1220 x 5 mm |
| Weight per package / per m2 | 22.5 kg / 9 kg |
| Area per package / per pallet | 2.5 m² / 110 m² |
| Joint | Uniclic® |
| Installation method | Floating |
| Floor heating | Yes |
| Wear leayer thickness | 0.55 mm |
| Warranty | 25 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|--------------|-------------------------------|
| Effect of furniture leg | EN ISO 16581 | No visible damage/Change |
| Reaction To Fire | EN13501-1 | Bfl-s1 |
| Thermal Resistance R-Value | | 0.032 (m2K/W) |
| Residual indentation EN ISO 24343-1 | | < 0.2 mm (*with underlayment) |

TECHNICAL PROPERTIES

| | | |
|----------------------------------|----------------|-------------------------------|
| Dimensional stability | EN ISO 23999 | < 0.1 % |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Effect of castor chair | EN 425 | Suitable |
| Resistance to bacteria and fungi | | Good |
| Impact sound reduction | EN ISO 10140 | 19 ΔLw dB (IXPE underlayment) |
| Commercial usage classification | EN 14354:2017 | Class 33 |



Other products in this collection



MARRONE CLW 228



OVERO CLW 228



TOBIANO CLW 228



SABIANO CLW 228



ROAN CLW 228