



OVERO CLW 228

Overo features a warm aged oak colour, which in combination with the visible knots, cracks and wood grain introduces a characteristic floor lifting up any interior by creating a warm and inviting space

PRODUCT DETAILS		FA
Article Number	LTCLW2404-228	
Design features	Microbevelled 4- sided	A
Dimensions	228 x 1220 mm	
Weight per Package	22.5 kg	
Area per Package	2.5 m ²	
Area per pallet	110 m²	
Construction	Click 5 mm	F

FACTS		
Design	Wood design	
Application area	Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality	
Features	Antistatic	
Format	Planks	
Range	Luxury Tiles	
Collection	Ranch Collection	
Joint	Uniclic®	
Floor heating	Yes	
Warranty	10 years	
Backside material	IXPE Sound reducing backing	
Thickness	5 mm	

Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Reaction To Fire	EN13501- 1	Bfl-s1	B _{rrt} 2
Thermal Resista Value	ance R-	0.032 (m2K/W)	
Residual indent	ation EN	< 0.2 mm (*with underlayment)	Tg.
Dimensional stability	EN ISO 23999	< 0.1 %	K 7
Colour fastness	EN ISO 105-B02	≥ 6	3,
Slip resistance	EN 13893	DS (>0.3)	**************************************
Slip resistance	DIN 51130	R10	92
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	F
Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	ř.C

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable	a
Resistance to ba	acteria and	Good	
Impact sound reduction	EN ISO 10140	19 Δ Lw dB (IXPE underlayment)
Commercial usage classification	EN 14354:201	Class 33 7	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















Other products in this collection







Overo CLW 228



Tobiano CLW 228



Sabiano CLW 228



Roan CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.













