



# CREMELLO CLW 228

With a creamy, cool, greyish base Cremello is inspired by the colouring of its namesake. The subtle shift in light grey nuances offers a soft variety on par with the clean, and calm wood design perfect for setting the basis for a subdued interior design.

## PRODUCT DETAILS

Article Number	LTCLW2410-228
Design features	Microbevelled 4-sided
Dimensions	228 x 1220 mm
Weight per Package	22.5 kg
Area per Package	2.5 m <sup>2</sup>
Area per pallet	110 m <sup>2</sup>
Construction	Click 5 mm

## FACTS

Design	Wood design
Application area	Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality
Features	Antistatic
Range	Luxury Tiles
Collection	Hacienda Collection
Joint	Uniclic®
Floor heating	Yes
Warranty	10 years
Backside material	IXPE Sound reducing backing
Thickness	5 mm
Installation method	Floating


## TECHNICAL PROPERTIES

Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.032 (m2K/W)	
Residual indentation EN ISO 24343-1		< 0.2 mm (*with underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	
Statcal electrical propensity	EN 1815	< 2 kV (antistatic)	
Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable	
Resistance to bacteria and fungi		Good	
Impact sound reduction	EN ISO 10140	19 ΔLw dB (IXPE underlayment)	
Commercial usage classification	EN 14354:2017	Class 33	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Palomino CLW 228



Amber CLW 228



Perlino CLW 228



Cremello CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.