

PERLINO CLW 228

Perlino offers a soft, pale greige colour with dark undertones and in combination with the calm, natural wood design creates a flooring design which will give any space a luxurious feel and impression

RODUCT DETAILS		FACTS		TECHNICAL PROPI	RTIES		
Article Number	LTCLW2411-228	Design	Wood design	Effect of	EN ISO	No visible	
Design features	Microbevelled 4- sided	Application area	Retail, Residential, Heavy commercial,	furniture leg Reaction To	16581 EN13501-	damage/Change Bfl-s1	Birst
Dimensions	228 x 1220 mm		Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality	Fire	1		
Weight per Package	22.5 kg			Thermal Resistance R- Value		0.032 (m2K/W)	
Area per Package	2.5 m ²	Features	Antistatic	Residual indentation EN < 0.2 mm (*with (stop 24343-1) underlayment)		< 0.2 mm (*with	
Area per pallet	110 m ²						
Construction	Click 5 mm	Format Range	Planks Luxury Tiles	Dimensional stability	EN ISO 23999	< 0.1 %	K N K N
		Collection	Hacienda Collection	Colour	EN ISO 105-B02	≥ 6	3 2
		Joint	Uniclic®	fastness	105-802		
		Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	OS-
		Warranty	10 years	Slip resistance	DIN 51130	R10	%
		Backside material	IXPE Sound reducing backing	Statical electrical	EN 1815	< 2 kV (antistatic)	Ž
		Thickness	5 mm	propensity		(artistatic)	
				Scratch resistance	EN16094	Pass with good results	
				Chemical resistance	EN ISO 26987	Pass with good results	€

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable	a
Resistance to ba	acteria and	Good	
Impact sound reduction	EN ISO 10140	19 Δ Lw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33 7	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















Other products in this collection









Palomino CLW 228

Amber CLW 228

Perlino CLW 228

Cremello CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.













