



DS (>0.3)

< 2 kV (antistatic)

19 **∆**Lw dB (IXPE underlayment)

Pass with good results

Pass with good results

R10

Good

Class 33

PERLINO CLICK 5 MM

Perlino offers a soft, pale-greige color with dark undertones, and in combination with the calm, natural wood design, creates a flooring design that will give any space a luxurious feel and impression.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	Slip resistance
Article Number / EAN Code	LTCLW2411-228 / 7393969302432	Slip resistance
Design	1-strip	Statical electrical
Width x Length x Thickness	228 x 1220 x 5 mm	propensity
Weight per package / per	22.5 kg / 9 kg	Scratch resistance
m2		Chemical resistance
Area per package / per	2.5 m ² / 110 m ²	Resistance to bacteria and
pallet		fungi
Joint	Uniclic®	Impact sound reduction
Installation method	Floating	
Floor heating	Yes	Commercial usage
Wear leayer thickness	0.55 mm	classification

1551	MISSION CLAS	
2	- S	
# M	IT)	
14.	.6	







EN 13893

DIN 51130

EN 1815

EN16094

EN ISO 26987

EN ISO 10140

EN 14354:2017







TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.032 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6

Other products in this collection









PALOMINO CLICK

AMBER CLICK

PERLINO CLICK

CREMELLO CLICK