



PERLINO CLW 228

Perlino offers a soft, pale greige color with dark undertones and in combination with the calm, natural wood design creates a flooring design which will give any space a luxurious feel











PRODUCT DETAILS

Article Number	LTCLW2411-228
Refining Treatment	Microbeveled 4-sided
Dimensions	9 x 48 "
Weight per Package	49.6 lbs
Area per Package	26.9 sqft
Area per pallet	1184 sqft
Construction	Click 5 mm

FACTS

Design	Wood design
Use	Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality
	Antistatic
	Planks
Range	Luxury Tiles
Collection	Hacienda Collection
Joint	Uniclic®
Floor heating	Yes
Backside material	IXPE Sound reducing backing
Thickness	1/4"
Installation method	Floating

TECHNICAL PROPERTIES

Reaction To Fire	EN13501- Bfl-s1 1	
Thermal Resistance R-Value	0.032 (m2K/W)	
Residual indentation	EN ISO 24343-1 < 0.2 mm (*with underlayment)	
Dimensional stability	EN ISO 23999 < 0.1 %	
Colour fastness	EN ISO 105-B02 ≥ 6	
Slip resistance	EN 13893 DS (>0.3)	
Slip resistance	DIN 51130 R10	
Statical electrical propensity	EN 1815 < 2 kV (antistatic)	
Scratch resistance	EN16094 Pass with good results	
Chemical resistance	EN ISO 26987 Pass with good results	
Resistance to bacteria and fungi	Good	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Impact sound reduction	EN ISO 10140	19 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Perlino CLW 228



Cremello CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.