



AMBER CLICK 5 MM

A combination of beige hues and contrasting darker nuances creates the soothing colour of Amber. This, and the subtle wood design combines into a floor which will provide a warm and relaxed atmosphere

| PRODUCT DETAILS | | | |
|-----------------------------|---|--------------------------|--|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Click SPC LVT | | |
| Article Number / EAN Code | LTCLW2412-228 / 7393969302449 | | |
| Design | Plank | | |
| Width x Length x Thickness | 228 x 1220 x 5 mm | | |
| Weight per package / per | 22.5 kg / 9 kg | | |
| m2 | | | |
| Area per package / per | 2.5 m ² / 110 m ² | | |
| pallet | | | |
| Joint | Uniclic® | | |
| Installation method | Floating | | |
| Floor heating | Yes | | |
| Wear leayer thickness | 0.55 mm | | |
| Warranty | 25 years | | |
| TECHNICAL PROPERTIES | | | |
| Effect of furniture leg | EN ISO 16581 | No visible damage/Change | |
| Emission of formaldehyde | | E1 | |
| Reaction To Fire | EN13501-1 | Bfl-s1 | |
| Formaldehyde Emission | EN717-1 | E1 | |

TECHNICAL PROPERTIES

| Thermal Resistance R-Value | | 0.032 (m2K/W) |
|----------------------------|----------------|-------------------------|
| Residual indentation EN | | < 0.2 mm (*with |
| ISO 24343-1 | | underlayment) |
| Dimensional stability | EN ISO 23999 | < 0.1 % |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Slip resistance | CEN/TS15676 | N/A |
| Statical electrical | EN 1815 | < 2 kV (antistatic) |
| propensity | | |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Effect of castor chair | EN 425 | Suitable |
| Resistance to bacteria and | | Good |
| fungi | | |
| Impact sound reduction | EN ISO 10140 | 19 ∆ Lw dB (IXPE |
| | | underlayment) |
| Commercial usage | EN 14354:2017 | Class 33 |
| classification | | |















Other products in this collection









PALOMINO CLICK

AMBER CLICK

PERLINO CLICK

CREMELLO CLICK