

EACTS



TECHNICAL DECDEDTIES

Scratch

resistance

Chemical resistance

AMBER CLW 228

DRODUCT DETAILS

A combination of beige hues and contrasting darker nuances creates the soothing colour of Amber. This, and the subtle wood design combines into a floor which will provide a warm and relaxed atmosphere

PRODUCT DETAILS		FACTS		TECHNICAL PROPI	ERTIES		
Article Number	LTCLW2412-228	Design	Wood design	Effect of	EN ISO	No visible	
Design features	Microbevelled 4- sided	Application area	Retail, Residential, Heavy commercial,	furniture leg Reaction To	16581 EN13501-	damage/Change Bfl-s1	e B _m s1
Dimensions	228 x 1220 mm		Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality	Fire	1		
Weight per Package	22.5 kg			Thermal Resistance R- Value		0.032 (m2K/W)	
Area per Package	2.5 m ²		Antistatic	Residual indentation EN < 0.2 mm (*with		1 =	
Area per pallet	110 m ²			ISO 24343-1 underlayment)			
Construction	Click 5 mm	Format	Planks	Dimensional	EN ISO	< 0.1 %	K N K N
		Range	Luxury Tiles	stability	23999		
		Collection	Hacienda Collection	Colour	EN ISO	≥ 6	%
		Joint	Uniclic®	fastness	105-B02		_
		Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	96 05
		Warranty	10 years	Slip resistance	DIN 51130	R10	75
		Backside material	IXPE Sound reducing backing	Statical electrical	EN 1815	< 2 kV (antistatic)	Ŧ
		Thickness	5 mm	propensity		,	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















EN16094 Pass with good

EN ISO

26987

results

results

Pass with good

TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable	a
Resistance to ba	acteria and	Good	
Impact sound reduction	EN ISO 10140	19 Δ Lw dB (IXPE underlayment)
Commercial usage classification	EN 14354:201	Class 33 7	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.















Other products in this collection









Palomino CLW 228

Amber CLW 228

Perlino CLW 228

Cremello CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.













