



AMBER CLICK 5 MM

A combination of beige hues and contrasting darker nuances creates the soothing color of Amber. This, and the subtle wood design combines into a floor which will provide a warm and relaxed atmosphere.

A combination of beige hues and contrasting darker nuances creates the soothing colour of Amber. This, and the subtle wood design combines into a floor which will provide a warm and relaxed atmosphere

PRODUCT DETAILS			
Product type / Construction	Vinyl Flooring / C	lick SPC LVT	
Article Number / EAN Code	LTCLW2412-228 / 7393969302449		
Design	1-strip		
Width x Length x Thickness	9 x 48 x 1/4"		
Weight per package / per	49.6 lbs / 19.8 lbs		
m2			
Area per package / per	26.9 sqft / 1184 sqft		
pallet			
Joint	Uniclic®		
Installation method	Floating		
Floor heating	Yes		
Wear leayer thickness	0"		
TECHNICAL PROPERTIES			
Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Emission of formaldehyde		E1	
Reaction To Fire	EN13501-1	Bfl-s1	
Formaldehyde Emission	EN717-1	E1	
Thermal Resistance R-Value		0.032 (m2K/W)	

Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Slip resistance	CEN/TS15676	N/A
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	19 ∆ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		













Other products in this collection









PALOMINO CLICK

AMBER CLICK

PERLINO CLICK

CREMELLO CLICK