

PALOMINO CLW 228

Palomino has a rich and deep natural oak golden-brown colour, and with the calm wood grading of the design it this floor effortlessly creates a comfy and cosy feel

RODUCT DETAILS		FACTS		TECHNICAL PROPI	ERTIES		
Article Number	LTCLW2413-228	Design	Wood design	Effect of	EN ISO	No visible	
Design features	Microbevelled 4- sided	Application area	Dication area Retail, Residential, Heavy commercial, Residential/Commercial, Residential and public spaces, Commercial, Office, Hospitality	furniture leg Reaction To	16581 EN13501-	damage/Change Bfl-s1	e Birst
Dimensions	228 x 1220 mm			Fire	1		
Weight per Package	22.5 kg			Thermal Resistance R- Value		0.032 (m2K/W)	G
Area per Package	2.5 m ²			Residual indentation EN< 0.2 mm (*withISO 24343-1underlayment)		< 0.2 mm (*with	í C
Area per pallet	110 m ²	Features	Antistatic				
Construction	Click 5 mm	Format	Planks	Dimensional	EN ISO 23999	< 0.1 %	רא רא
		Range	Luxury Tiles	stability			
		Collection	Hacienda Collection	Colour	EN ISO 105-B02	≥ 6	Ŗ
		Joint	Uniclic®	fastness			
		Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	Non-
		Warranty	10 years	Slip resistance	DIN 51130	R10	PA- DS
		Backside material	IXPE Sound reducing backing	Statical	EN 1815	< 2 kV (antistatic)	Ŷ
		Thickness	5 mm	propensity		(מוזנואנטוני)	
				Scratch resistance	EN16094	Pass with good results	F
				Chemical resistance	EN ISO 26987	Pass with good results	\$ 0

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

Effect of castor chair	EN 425	Suitable
Resistance to ba fungi	acteria and	Good
Impact sound reduction	EN ISO 10140	19 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



18.05.2024 AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2023

Other products in this collection



Palomino CLW 228



Amber CLW 228



Perlino CLW 228



Cremello CLW 228

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

