

OAK NOUVEAU WHITE

The soft white stain on this single-strip, white oak floor from the Classic Nouveau Collection has an even expression, lightly peppered with small knots and cracks. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|---|---|----------------------|-------------------------------|--------------------------|---|-----------|
| Article Number | 151L8AEK1DKW220 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969047562 | Design | 1-strip | content | | |
| Surface treatment | Matt lacquer | Grading | Lively | Minimun Mean | Minimun Mean Density kg/m ³ >500 kg/m ³ | |
| Design features | Bevelled 4-sided, | Range | Kährs Original | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Dimensions | Brushed 187 x 2266 mm | Collection | Classic Nouveau Collection | Formaldehyde Emission | EN717-1 | E1 |
| Weight per Package | 21 kg | Resandable | 2-3 times | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Area per Package | 2.5 m ² | Natural/Stained | Stained | Breaking | EN1533 | NPD |
| Area per pallet | 114.3 m ² | Brinell Value | 3,7 | Strength | | |
| Package info | Packages may contain start and stop boards. | Joint | Woodloc® 5S | N/mm ² | | |
| | | Floor heating | Yes | Thermal Conductivity | EN12664 | 0,14 W/mK |
| DETAIL DESCRIPTION | | Warranty | 30 years | Thermal Resista | Thermal Resistance R-Value | |
| All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | Warranty US | 25 years | Biological | EN350-2 | Class 1 |
| | | Wear-layer material | Hardwood | Durability | | |
| | | Wear Layer Thickness | 3.5 mm | CARB2 | CARB2 | |
| | | Core material | Pine/Spruce lamella | Slipperiness | Slipperiness CEN/TS15676 | |
| | | Thickness | 15 mm | | | |
| Stained product - noticable color change over time. | | Installation method | Floating, Glue-down | | | |
| | | Surface Colour | White 1D | | | |

Other products in this collection




Oak Nouveau Whisper





Oak Nouveau Lace





Oak Nouveau Snow

Oak Nouveau Gray

Oak Nouveau Black

CERTIFICATES





All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Oak Nouveau Rich

Oak Nouveau Greige



Oak Nouveau Blonde



Oak Nouveau White