



OAK ROCHFORD

DDODLICT DETAILS

The tan hues found in this single-strip oak floor from the European Naturals Collection are complemented with knots and cracks, resulting in a timeless rustic expression. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DETAILS | | PRODUCT DE |
|-----------------------------|--|------------------|
| Product type / Construction | Wood Floors / 3-layer parquet | Hardness (Brine |
| Article Number / EAN Code | 151N9AEK09KW220 / 7393969302784 | range |
| Design / Wood Species | 1-strip / Oak | Warranty |
| Surface treatment / | Matt lacquer / Natural | TECHNICAL P |
| Natural/Stained | | — Moisture conte |
| Design features | Brushed, Microbevelled 4-sided | — Minimun Mean |
| Width x Length x Thickness | 187 x 2266 x 15 mm | — kg/m³ |
| Weight per package / per | 21 kg / 8.27 kg | Reaction To Fire |
| m2 | | Formaldehyde |
| Area per package / per | 2.54 m ² / 114.3 m ² | Content PCP |
| pallet | | |
| Grading | Dynamic | Breaking Streng |
| Joint | Woodloc® 5S | Thermal Condu |
| Installation method | Floating, Glue-down | Biological Dura |
| Floor heating | Yes | CARB2 |
| Wear leayer material / | Hardwood / 3.5 mm | Slip resistance |
| thickness | | TSCA |
| Resandable | 2-3 times | CARB P2 |
| Core material | Pine/Spruce/Alder | Compliant |
| Backside material | Spruce | floor |

| PROD | UCT L | ETAILS |
|------|-------|--------|
| | | |

| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 |
|----------------------------|-----------------|
| range | |
| Warranty | 30 years |
| TECHNICAL PROPERTIES | |
| · | |

| Moisture content | EN13183 | 7%±2% |
|--------------------------------------|-------------|------------|
| Minimun Mean Density | | >500 kg/m³ |
| – kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| — CARB2 | _ | Compliant |

CEN/TS15676













NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection

