



OAK CORTINA

DDODLICT DETAIL C

This light 3-strip floor has a clean look with modern contrasts between lighter and darker elements. The white stain overlays these contrasts, ensuring a unified base for any interior. Each board is carefully brushed to enhance the natural character of the grain and the ultra-matt lacquer finish effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value	
Article Number / EAN Code	133N0BEKM4KW240 / 7393969302647	range	
Design / Wood Species	3-strip / Oak	LRV / LRV Std1 / LRV Std	
Surface treatment /	Ultra matt lacquer / Stained	Warranty	
Natural/Stained		— TECHNICAL PROPER	
Design features	Brushed	Moisture content	
Width x Length x Thickness	200 x 2423 x 13 mm	Minimun Mean Density	
Weight per package / per	24.5 kg / 7.21 kg	kg/m ³	
m2		— Reaction To Fire	
Area per package / per	3.4 m ² / 170 m ²	Formaldehyde Emissio	
pallet		— Content PCP	
Grading	Lively	Breaking Strength N/m	
Joint	Woodloc® 5G	Thermal Conductivity	
Installation method	Floating, Glue-down	Biological Durability	
Floor heating	Yes	— CARB2	
Wear leayer material /	Hardwood / 2.6 mm		
thickness		Slip resistance	
Resandable	2-3 times	TSCA SENANCO	
Core material	Pine/Spruce/Alder	CARB P2	
Backside material	Veneer	Compliant	

F	PRO	DU	ICT	DE	ΓΑΙ	LS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1 / LRV Std2	54 / 5.8 / 11.6	
Warranty	20 years	
TECHNICAL PROPERTIES		
- Moisture content	EN13183	7%±2%

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Conductivity Biological Durability	EN12664 EN350-2	0,11W/mK Class 1







CEN/TS15676





NPD



DETAILED DESCRIPTION

Significant wood colour variations allowed, from light to dark brown. Includes sapwood. Medium sound and small black knots may occur.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection

OAK ERVE OILED

OAK LECCO SATIN

