



## OAK CORTINA

This light 3-strip floor has a clean look with modern contrasts between lighter and darker elements. The white stain overlays these contrasts, ensuring a unified base for any interior. Each board is carefully brushed to enhance the natural character of the grain and the ultra-matt lacquer finish effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) va	
Article Number / EAN Code	133N0BEKM4KW240 / 7393969302647	range	
Design / Wood Species	3-strip / Oak	LRV / LRV Std1 / LRV	
Surface treatment /	Ultra matt lacquer / Stained	Warranty	
Natural/Stained		TECHNICAL PROPI	
Design features	Brushed	Moisture content	
Width x Length x Thickness	200 x 2423 x 13 mm	— Minimun Mean Dens	
Weight per package / per	24.5 kg / 7.21 kg	kg/m <sup>3</sup>	
m2		Reaction To Fire	
Area per package / per	3.4 m <sup>2</sup> / 170 m <sup>2</sup>	Formaldehyde Emiss	
pallet		— Content PCP	
Grading	Lively	Breaking Strength N/	
Joint	Woodloc® 5G	— Thermal Conductivity	
Installation method	Floating, Glue-down	Biological Durability	
Floor heating	Yes	— CARB2	
Wear leayer material /	Hardwood / 2.6 mm	Slip resistance	
thickness		<del>.</del>	
Resandable	2-3 times	TSCA TITLE VI	
Core material	Pine/Spruce/Alder	EPD) TITLE VI CARB P2 Compliant	
Backside material	Veneer		

PRC	יטענ	LIL	EIA	LS

Hardness (Brinell) value /	3,//2.2 - 5.9
range	
LRV / LRV Std1 / LRV Std2	54 / 5.8 / 11.6
Warranty	20 years

## PERTIES

TECHNICAL FROTERILES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











## **DETAILED DESCRIPTION**

Significant wood colour variations allowed, from light to dark brown. Includes sapwood. Medium sound and small black knots may occur.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection

OAK ERVE OILED

OAK LECCO SATIN

