

## OAK NOUVEAU BLONDE

The semi-transparent stain on this single-strip, white oak floor from the Classic Nouveau Collection allows the warmer hues to come through, giving the floor a light colour balance and a classically Nordic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided micro-bevelling at the edges ensures a traditional full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PRO	TECHNICAL PROPERTIES		
Article Number	151N8AEKP1KW220	Wood Species	Oak	Moisture	EN13183	7%±2%	
EAN Code	7393969043953	Design	1-strip	content			
Surface treatment	Matt lacquer	Grading	Lively	Minimun Mean Density kg/m <sup>3</sup> >500 kg/m <sup>3</sup>			
Design features	Brushed, Microbevelled	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1	
Dimensions	4-sided 187 x 2266 mm	Collection	Classic Nouveau Collection	Formaldehyde Emission	EN717-1	E1	
Weight per Package	21 kg	Resandable	2-3 times	Content PCP	CEN/TR14823	≤ 5 ppm	
Area per Package	2.54 m <sup>2</sup>	Natural/Stained	Stained	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD	
Area per pallet	114.3 m <sup>2</sup>	Brinell Value	3,7				
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5S		EN12664	0,14 W/mK	
		Floor heating	Yes	<ul> <li>Thermal</li> <li>Conductivity</li> </ul>			
DETAIL DESCRIPTION		Warranty	30 years	Thermal Resista	Thermal Resistance R-Value		
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Warranty US	25 years	Biological	EN350-2	Class 1	
		Wear-layer material	Hardwood	Durability			
		Wear Layer Thickness	3.5 mm	CARB2		Compliant	
		Core material	Pine/Spruce lamella	Slipperiness	CEN/TS15676	5676 NPD	
COLOUR CHANGE		Backside material	Spruce				
Stained product - noticable color change over time.		Thickness	15 mm				
		Installation method	Floating, Glue-down				
		Surface Colour	White				
		LRV	54				

## Other products in this collection




Oak Nouveau Whisper





Oak Nouveau Lace





Oak Nouveau Snow

Oak Nouveau Gray

Oak Nouveau Black

## CERTIFICATES





All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Oak Nouveau Rich

Oak Nouveau Greige



Oak Nouveau Blonde



Oak Nouveau White