



OAK PARIS ULTRA MATT 242

The blonde nuances in this white, single-strip floor from the Capital Collection are balanced by an even colour variation between planks. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

| Article Number / EAN Code 151N4AEK4JKW240 / 7393969046077 Design / Wood Species 1-strip / White Oak Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | PRODUCT DETAILS | | |
|---|-----------------------------|------------------------------------|--|
| Design / Wood Species Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Product type / Construction | Wood Flooring / 3-layer engineered | |
| Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Article Number / EAN Code | 151N4AEK4JKW240 / 7393969046077 | |
| Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Design / Wood Species | 1-strip / White Oak | |
| Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Surface Treatment / | Ultra matt lacquer / Stained | |
| Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Natural/Stained | | |
| Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Refining Treatment | Microbeveled 4-sided, Brushed | |
| Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Width x Length x Thickness | 7 3/8 x 95 1/4 x 5/8" | |
| Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Weight per package / per | 52.9 lbs / 19.4 lbs | |
| pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | m2 | | |
| Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Area per package / per | 29.3 sqft / 1317.5 sqft | |
| Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | pallet | | |
| Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Grading | Calm | |
| Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Joint | Woodloc® 5S | |
| Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Installation method | Floating, Glue-Down | |
| thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Floor heating | Yes | |
| Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Wear leayer material / | Hardwood / 1/8" | |
| Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | thickness | | |
| Hardness (Brinell) value / 3,7 / 2.2 - 5.9 | Resandable | 2 times | |
| | Core material | Pine/Spruce lamella | |
| range | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| range | range | | |

| PRODUCT DETAILS | |
|-----------------|--|
| LRV / LRV Std1 | |

| LRV / LRV Std1 | 38 / 3.5 | |
|-------------------------------------|-------------|-------------|
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Resistance R-Value | 2 | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |











DETAILED DESCRIPTION

Even colour with minor variations

Small sized knots in limited numbers allowed.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection







Oak Prague



Oak Berlin



OAK DUBLIN OILED