



OAK PARIS ULTRA MATT 242

The blonde nuances in this white, single-strip floor from the Capital Collection are balanced by an even colour variation between planks. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

Article Number / EAN Code 151N4AEK4JKW240 / 7393969046077 Design / Wood Species 1-strip / White Oak Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	PRODUCT DETAILS			
Design / Wood Species Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Product type / Construction	Wood Flooring / 3-layer engineered		
Surface Treatment / Ultra matt lacquer / Stained Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Article Number / EAN Code	151N4AEK4JKW240 / 7393969046077		
Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Design / Wood Species	1-strip / White Oak		
Refining Treatment Microbeveled 4-sided, Brushed Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Surface Treatment /	Ultra matt lacquer / Stained		
Width x Length x Thickness 7 3/8 x 95 1/4 x 5/8" Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Natural/Stained			
Weight per package / per 52.9 lbs / 19.4 lbs m2 Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Refining Treatment	Microbeveled 4-sided, Brushed		
Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"		
Area per package / per 29.3 sqft / 1317.5 sqft pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Weight per package / per	52.9 lbs / 19.4 lbs		
pallet Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	m2			
Grading Calm Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Area per package / per	29.3 sqft / 1317.5 sqft		
Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	pallet			
Installation method Floating, Glue-Down Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Grading	Calm		
Floor heating Yes Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Joint	Woodloc® 5S		
Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Installation method	Floating, Glue-Down		
thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Floor heating	Yes		
Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Wear leayer material /	Hardwood / 1/8"		
Core material Pine/Spruce lamella Hardness (Brinell) value / 3,7 / 2.2 - 5.9	thickness			
Hardness (Brinell) value / 3,7 / 2.2 - 5.9	Resandable	2 times		
	Core material	Pine/Spruce lamella		
range	Hardness (Brinell) value /	3,7 / 2.2 - 5.9		
range	range			

PR	OD	UCI	DE	IAIL	.5

LRV / LRV Std1	38 / 3.5	
TECHNICAL PROPERTIES	S	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











DETAILED DESCRIPTION

Even colour with minor variations

Small sized knots in limited numbers allowed.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection







OAK PARIS ULTRA MATT



Oak Prague



Oak Berlin