



ASH GOTLAND

European Ash, one strip, silk matte finish, significant color variation. Lively, rustic, some knots.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	151L87AK50KW220 / 7393969048156
Design / Wood Species	1-strip / Ash
Surface Treatment / Natural/Stained	Silk matte finish / Natural
Width x Length x Thickness	7 3/8 x 89 1/4 x 5/8"
Weight per package / per m2	46.3 lbs / 18.2 lbs
Area per package / per pallet	27.3 sqft / 1230.3 sqft
Grading	Lively
Joint	Woodloc® 5S
Installation method	Glue-Down, Floating
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value / range	4,0 / 2.8 - 6.2
Warranty	25 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.
The product includes large sound and black knots. Knots may vary in size and numbers.
Colour change: Pale cream darkens to straw tan.
Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Beech Viborg



Ash Gotland