



OAK PRAGUE

The grey notes in this single-strip floor from the Capital Collection are balanced by an even color variation between planks. Only the finest quality oak timber is used, and each board is brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of a newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided micro-beveling at the edges ensures a classic, full plank look and feel.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--------------------|---|--|---------------------|---------------------------------------|-------------|-----------|
| Article Number | 151N4AEKD4KW240 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| EAN Code | 7393969046930 | Design | 1-strip | Minimum Mean Density kg/m³ >500 kg/m³ | | |
| Surface treatment | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. | Grading | Calm | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| | | Collection | Capital Collection | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Design features | Microbevelled 4-sided, Brushed | Resandable | 2-3 times | Breaking Strength N/mm² | EN1533 | NPD |
| Dimensions | 187 x 2420 mm | Natural/Stained | Stained | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Weight per Package | 22 kg | Brinell Value | 3,7 | Thermal Resistance R-Value | .11 (m2K/W) | |
| Area per Package | 2.72 m² | Joint | Woodloc® 5S | Biological Durability | EN350-2 | Class 1 |
| Area per pallet | 122.4 m² | Floor heating | Yes | CARB2 | Compliant | |
| Package info | Packages may contain start and stop boards. | Warranty | 30 years | Slipperiness | CEN/TS15676 | NPD |
| | | Warranty US | 25 years | | | |
| | | Wear-layer material | Hardwood | | | |
| | | Wear Layer Thickness | 3.5 mm | | | |
| | | Core material | Pine/Spruce/Alder | | | |
| DETAIL DESCRIPTION | | Backside material | Spruce | | | |
| | | Thickness | 15 mm | | | |
| | | Installation method | Floating, Glue-down | | | |
| COLOUR CHANGE | | Surface Colour | Grey | | | |
| | | Stained product - noticeable color change over time. | | | | |

Other products in this collection



Oak Prague



Oak Berlin



Oak Paris



Oak Dublin

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.