



OAK PURE

The warm taupe nuances in this exclusive, single-strip floor from the Element Collection are enhanced by an even colour variation between planks and a sweeping natural grain. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the timber and highlight the texture of the wood.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 151N5AEK09KW200 / 7393969045513 |
| Design / Wood Species | 1-strip / Oak |
| Surface treatment / Natural/Stained | Matt lacquer / Natural |
| Design features | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness | 151 x 2000 x 15 mm |
| Weight per package / per m2 | 15 kg / 8.29 kg |
| Area per package / per pallet | 1.81 m ² / 97.74 m ² |
| Grading | Lively |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce/Alder |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | |
|----------------|----------|
| LRV / LRV Std1 | 35 / 5.1 |
| Warranty | 30 years |

TECHNICAL PROPERTIES

| | | |
|--|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m ³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2024-12-09

Other products in this collection



Oak Cinder



Oak Crisp



Oak Bright



Oak Pure