



## OAK PARIS

The blonde nuances in this white, single-strip floor from the Capital Collection are balanced by an even colour variation between planks. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

### PRODUCT DETAILS

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Product type / Construction         | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code           | 151N4AEK4JKW200 / 7393969304429    |
| Design / Wood Species               | 1-strip / White Oak                |
| Surface Treatment / Natural/Stained | Ultra matt lacquer / Stained       |
| Refining Treatment                  | Microbeveled 4-sided, Brushed      |
| Width x Length x Thickness          | 7 3/8 x 78 3/4 x 5/8"              |
| Weight per package / per m2         | 39.7 lbs / 18.5 lbs                |
| Area per package / per pallet       | 24.1 sqft / 1085 sqft              |
| Grading                             | Calm                               |
| Joint                               | Woodloc® 5S                        |
| Installation method                 | Floating, Glue-Down                |
| Floor heating                       | Yes                                |
| Wear leayer material / thickness    | Hardwood / 1/8"                    |
| Resandable                          | 2 times                            |
| Core material                       | Pine/Spruce lamella                |
| Hardness (Brinell) value / range    | 3,7 / 2.2 - 5.9                    |

### PRODUCT DETAILS

|                             |                         |
|-----------------------------|-------------------------|
| LRV / LRV Std1              | 38 / 3.5                |
| Warranty                    | 25 years                |
| <b>TECHNICAL PROPERTIES</b> |                         |
| Moisture content            | EN13183 7%±2%           |
| Minimun Mean Density kg/m³  | >500 kg/m³              |
| Reaction To Fire            | EN13501-1 Dfl-s1        |
| Formaldehyde Emission       | EN717-1 E1              |
| Content PCP                 | CEN/TR14823 ≤ 5 x 10-6n |
| Breaking Strength N/mm²     | EN1533 NPD              |
| Thermal Conductivity        | EN12664 0,14 W/mK       |
| Thermal Resistance R-Value  | .11 (m2K/W)             |
| Biological Durability       | EN350-2 Class 1         |
| CARB2                       | Compliant               |
| Slip resistance             | CEN/TS15676 NPD         |



### DETAILED DESCRIPTION

Even colour with minor variations.  
Small sized knots in limited numbers allowed.

**Ultra matt lacquer:** The appearance of the matte surface may vary due to different light sources and angles.

**Colour change:** Stained product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |  
www.kahr.com | ©Kährs,  
USA & Canada 2024-12-01

## Other products in this collection



Oak Prague



Oak Berlin



Oak Paris



Oak Dublin