



# OAK TRAMONTANE

The darker grey stain of Oak Tramontane gives this floor a refined yet rustic expression perfect for any interior, where one wants to create a warm yet sophisticated impression. The careful brushing of each plank brings out the natural wood grain while the contrast of the darker knots and cracks are softened by the overall warm, dark stain. This without diminishing the effect of these natural design elements featured in each wide plank.

The darker grey stain of Oak Tramontane gives this floor a refined yet rustic expression perfect for any interior, where one wants to create a warm yet sophisticated impression. The careful brushing of each plank brings out the natural wood grain while the contrast of the darker knots and cracks are softened by the overall warm, dark stain. This without diminishing the effect of these natural design elements featured in each wide plank.

## PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	141XCDEKFMKW225 / 7393969304467
Design / Wood Species	1-strip / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed, Smoked
Width x Length x Thickness	220 x 2200 x 14 mm
Weight per package	22.8 kg
Area per package / per pallet	2.9 m <sup>2</sup> / 127.78 m <sup>2</sup>
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 2.5 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9

## PRODUCT DETAILS

Warranty	30 years	
<b>TECHNICAL PROPERTIES</b>		
Moisture content	EN13183	7%±2%
Minimum Mean Density	>500 kg/m <sup>3</sup>	
kg/m <sup>3</sup>		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Biological Durability	EN350-2	Class 1



## DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

**Oil:** This floor should be oiled immediately after installation.


**Colour change:** Smoked product - noticeable color change over time.

Packages may contain start and stop boards.

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection




OAK BOREAS




OAK EURUS




OAK MISTRAL



OAK SIROCCO



OAK ZEPHYR



OAK TRAMONTANE



OAK LEVANTER