



OAK EURUS

The light, warm, honey-tones of Oak Eurus showcases the unstained and beautiful oak of each plank. It allows the design features that nature has provided, such as the wood grain, knots and cracks to softly contrast with darker toffee nuances against the natural, softly brushed oak wood.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	141XDDEKF0KW225 / 7393969304504	
Design / Wood Species	Plank / Oak	
Surface treatment /	Oil / Natural	
Natural/Stained		
Design features	Microbevelled 4-sided, Brushed	
Width x Length x Thickness	220 x 2200 x 14 mm	
Weight per package	23 kg	
Area per package / per	2.904 m ² / 127.78 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 2.5 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

TRODUCT DETAILS		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD

EN12664

EN350-2





Thermal Conductivity

Biological Durability

PRODUCT DETAILS

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

0,14 W/mK

Class 1

Other products in this collection







OAK BOREAS

OAK EURUS

OAK MISTRAL