



OAK BOREAS

Oak Boreas intermingles colder, whiter tones with elements of slightly warmer, darker features such as knots and cracks creating a variety of shades for a natural, rustic look reminiscent of a freshly-cut oak. It is further enhanced by the careful brushing which accentuates the wood grain of each, unique wide plank.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	141XDDEKF1KW225 / 7393969304511
Design / Wood Species	Plank / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	220 x 2200 x 14 mm
Weight per package	23 kg
Area per package / per	2.904 m ² / 127.78 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

30 years	
EN13183	7%±2%
	>500 kg/m³
EN13501-1	Dfl-s1
EN717-1	E1
CEN/TR14823	≤ 5 ppm
EN1533	NPD
EN12664	0,14 W/mK
EN350-2	Class 1
	EN13183 EN13501-1 EN717-1 CEN/TR14823 EN1533 EN12664





DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection







OAK BOREAS

OAK EURUS

OAK MISTRAL