



OAK BOREAS

Oak Boreas intermingles colder, whiter tones with elements of slightly warmer, darker features such as knots and cracks creating a variety of shades for a natural, rustic look reminiscent of a freshly-cut oak. It is further enhanced by the careful brushing which accentuates the wood grain of each, unique wide plank.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 141XDDEKF1KW225 / 7393969304511 |
| Design / Wood Species | 1-strip / Oak |
| Surface Treatment / Natural/Stained | Oil / Stained |
| Refining Treatment | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness | 220 x 2200 x 14 mm |
| Weight per package | 22.8 kg |
| Area per package / per pallet | 2.9 m ² / 127.78 m ² |
| Grading | Dynamic |
| Joint | Woodloc® 5G |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 2.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce lamella |
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | | |
|-------------------------------------|------------------------|--------------------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Biological Durability | EN350-2 | Class 1 |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2025-04-17

Other products in this collection



OAK BOREAS



OAK EURUS



OAK MISTRAL