



## OAK CLOVES PLANK

Oak Cloves, with its rich color, brings depth and warmth to any interior. The smoky tones accentuate the natural grain, creating a sophisticated and warm ambiance. Perfect for adding a touch of elegance, timeless yet spicy character to your space.

| PRODUCT DETAILS             |                                |  |
|-----------------------------|--------------------------------|--|
| Product type / Construction | Wood Flooring / Veneer floors  |  |
| Article Number / EAN Code   | LTCLRW4003-193 / 7393969304597 |  |
| Design / Wood Species       | 1-strip / White Oak            |  |
| Surface Treatment /         | Ultra matt lacquer / Stained   |  |
| Natural/Stained             |                                |  |
| Refining Treatment          | Beveled 4-sided, Brushed       |  |
| Width x Length x Thickness  | 7 5/8 x 78 x 3/8"              |  |
| Weight per package          | 53.6 lbs                       |  |
| Area per package / per      | 28.8 sqft / 1439.7 sqft        |  |
| pallet                      |                                |  |
| Grading                     | Calm                           |  |
| Joint                       | Woodloc® 5G                    |  |
| Installation method         | Floating, Glue-Down            |  |
| Floor heating               | Yes                            |  |
| Wear leayer material /      | Hardwood / 0"                  |  |
| thickness                   |                                |  |
| Resandable                  | No                             |  |
| Core material               | HDF                            |  |
| Backside material           | Veneer                         |  |

| PRODUCT DETAILS            |             |             |
|----------------------------|-------------|-------------|
| LRV / LRV Std1 / LRV Std2  | 24/2/4      |             |
| TECHNICAL PROPERTIES       | )           |             |
| Emission of formaldehyde   |             | E1          |
| Moisture content           | EN13183     | 7%±2%       |
| Minimun Mean Density       |             | >800 kg/m³  |
| kg/m³                      |             |             |
| Reaction To Fire           | EN13501-1   | Bfl-s1      |
| Formaldehyde Emission      | EN717-1     | E1          |
| Content PCP                | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm²    | EN1533      | NPD         |
| Thermal Conductivity       | EN12664     | 0,15 W/mK   |
| Thermal Resistance R-Value |             | .07 (m2K/W) |
| Biological Durability      | EN350-2     | Class 1     |
| CARB2                      |             | Compliant   |





## DETAILED DESCRIPTION

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Packages may contain start and stop boards.

## Other products in this collection



OAK SAFFRON PLANK



OAK CUMIN PLANK



OAK PEPPER PLANK



OAK TURMERIC PLANK



OAK CARDAMOM PLANK



OAK CLOVES PLANK



OAK GINGER PLANK



OAK NUTMEG PLANK